



DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

Tempo Transition Primer

PRODUCT DESCRIPTION

Acrylic copolymer emulsion-based, top coat transition primer with high adherence.

FEATURES

Improves adherence by playing a binding bridge role between the paint and the surface. Reduces paint consumption by preventing over absorption of the top coat paint by the surface. Used for transition purposes in water-based applications on synthetic-based paints.

APPLICATION SURFACES

Used as a transition primer before application of water-based paints on synthetic-based paints. May be used as a primer on exposed concrete, smooth and rough plasters, mineral-based surfaces, and faded self-supporting silicone or acrylic-based previously painted surfaces.

APPLICATION

Application surfaces should be smooth, dry, clean, solid, and able to bear the paint. Remove any dirt, dust, mold grease and loose layers from the application surface, perform required surface corrections and prime with Tempo Transition Primer before application. Comply with defined setting periods on concrete, exposed concrete and new plastered surfaces (28 days).

Dull the surface with sand paper before moving on to a water-based paint on previously painted/new synthetic painted surfaces and for glossy, silky-matte, semi-matte water-based paints (before primer application).

Ensure that ambient and surface temperatures are between +5 °C and 30 °C during application. Apply using a brush, roller or spray gun. Our products should be applied on substructure surfaces that are built in line with 30.06.2007 dated General Construction Specifications No. 26568.

Airless Spraying:

Pressure: 140 bar

Nozzle Angle: 50°

Nozzle Size (inch): 0.013"

Thinning (Water): 5% (Volume)

THINNING RATIO

Thin by 10% maximum with water in brush and roller applications. Thin by 5% maximum with clean water in spray gun applications.

DRYING TIME (at 20 °C, 65% RH):

Touch dry: 1-2 hours

Paint application: 6 hours

Application on synthetic-based paint: 24 hours

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr



CONSUMPTION

9 m² area can be primed in a single coat with 1 kg. It can be change due to surface kind, thinning ratio , weather conditions and painter. Perform a controlled sample run to estimate the precise consumption.

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frost and direct sunlight.

PACKAGING

20 kg, 3.5 kg

WARNING WORD

Hazard

HAZARD PHRASE

H315 Causes skin irritation.

H318 Serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause irritation in respiratory tract.

PRECAUTIONARY PHRASES

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P305 + P351 + P338 IN CASE OF EYE CONTACT: Carefully rinse with water for a couple of minutes. Remove contact lenses if worn and easy to do so. Continue rinsing.

P310 Immediately CALL NATIONAL POISON CONSULTING CENTER AT 114/Call a doctor.

P321 Specific treatment required (see label).

P405 Keep locked up.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr

**Pose No.**

15.540.1205, 15.540.1206, 15.540.1207, 15.540.1211, 15.540.1214, 15.540.1215, 15.540.1217, 15.540.1218, 15.540.1220, 15.540.1221, 15.540.1232, 15.540.1233, 15.540.1301, 15.540.1302, 15.540.1303

Rate No.

10.300.1151

This technical sheet is prepared based on laboratory data at normal conditions, consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change this information.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

Rev1 2021

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr