



DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

Tempo Transparent Primer

PRODUCT DESCRIPTION

Ready-to-use, acrylic-based, transparent interior primer.

FEATURES

Tempo Transparent Primer forms a binding bridge between the paint and the surface. Prevents absorption of plaster surface thanks to its high penetration, enables the paint to integrate with the surface, prevents early drying of the paint and reduces paint consumption.

APPLICATION SURFACES

Applied as a precoat before paint on sateen plaster, plaster, lime, whitewash surfaces, surfaces that will be painted for the first time or are of low-quality, absorbent, plastic painted surfaces that lost their quality and highly absorbing and/or dust generating surfaces like aerated concrete.

APPLICATION

Ensure that the application surface is smooth, solid, and able to bear the primer and top-coat paint. Clean any stain, dust, loose layers and mold grease, and perform required surface corrections. Comply with defined setting periods on concrete, exposed concrete and new plastered surfaces (28 days).

Apply Tempo Transparent Primer on plaster or similar surfaces only after they are sanded and dusted with a moist cloth/moist car wash brush. Ensure that the ambient and surface temperatures are between +5 °C and +30 °C during application and until the product is fully dry, and protect the surfaces against frost. Apply Tempo Transparent Primer in a single coat using a brush or roller without combing/finishing (by rolling the roller one turn in one direction) in a way that will prevent formation of a glassy thin film layer on the surface. Dull the surface with sandpaper if a glassy surface is formed. Avoid airless spraying method. Our products should be applied on substructure surfaces that are built in line with 30.06.2007 dated General Construction Specifications No. 26568.

THINNING RATIO

Ready to use.

DRYING TIME (at 20 °C, 65% RH):

Touch dry: 1 hour

Paint application: 6 hours

CONSUMPTION

13,5 m² area can be primed in a single coat with 1 Liter. It can be change due to surface kind, thinning ratio , weather conditions and painter. Perform a controlled sample run to estimate the precise consumption.

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr



STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frost and direct sunlight.

PACKAGING

20 L, 5 L

WARNING WORD

Caution

HAZARD PHRASE

H317 May cause an allergic skin reaction.

PRECAUTIONARY PHRASES

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment required (see label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Pose No.

15.540.1216, 15.540.1219, 15.540.1222, 15.540.1234

Rate No.

10.300.1151

This technical sheet is prepared based on laboratory data at normal conditions, consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change this information.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

Rev1 2021

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr